



Application of AGT™ Stone

Specially formulated for ALL cement/concrete surface applications

It can be:

- Hand-broadcasted/Seeded onto a setting concrete slab.
- Spray adhesive to the inside of a concrete/cement Form and 'seeded'.
- Mixed directly into your Finish Surface Batch of your Concrete Countertop.
- Ground & Polished to any level of finish from ext. pathway 100 grit to mirror 3000 grit.
- Sealed as you would usually seal your cement/concrete projects.

Application of AGT™ Sand

Specially formulated for epoxy flooring, Stucco, & Cementitious Overlay applications

It can be:

- Hand-broadcasted/Seeded onto epoxy similar to seeding color flakes.
- Spray adhesive to the inside of a concrete/cement Form and 'seeded'.
- Mixed directly into stuccos & topcoat mixes.
- Ground & Polished to any level of finish from ext. pathway 100 grit to mirror 3000 grit.
- Sealed as you would usually seal your cement/concrete projects.
- This product works VERY WELL with solvent-based mixes i.e. epoxies.

PLEASE NOTE:

AGT™ Sand & Powder loading ratios vary based on required glow intensity & duration. It is suggested that you create a test sample panels or boards to establish the level of glow they would like to achieve.

Please feel free to contact us with you comments and suggestions. Send us a picture of any project using AGT™. The most unique projects will be highlighted on the AGT™ website with a short summary of your company and services. You will also be awarded a 1lb. pkg. of AGT™!!!!